

Polarbar minibars

Quality engineered with absorption cooling technology, this super quiet unit will please your guests all day and all night! Stylishly designed, with exceptionally generous internal cabinet space, these minibars are the perfect complement to a great hotel room.

Standard features include a lock and an inside light. These minibars are available in three different sizes with two types of glass doors as an option, for better product visibility and increased guest use.

STANDARD FEATURES

- : Stocking capacity of up to 38 facings
- : Transparent door racks for high visibility
- : Removable shelving for easy cleaning
- : Thermal insulation manufactured with cyclopentane.
- : Fully automated defrost and easily adjustable thermostat
- : Strong door hinges convertible left to right
- : All-round magnetic seals to keep the door perfectly shut
- : Integrated door handles
- : Interior LED light
- : Lock (can be deactivated)
- : Available sizes are 30, 40 and 60L
- : 3 different door options available
- : ISO 9001 2015 / ISO 14001 2015 CE

OPTIONAL FOR STANDARD MODEL:

- : Black plastic framed glass door
- : Aluminum framed glass door



PB Standard (Black Framed Glass Door)



PBD 42 (Drawer Unit)

NEW DRAWER UNIT

- : Stocking capacity of up to 38 facings
- : Transparent door racks for high visibility
- : Removable shelving for easy cleaning
- : Thermal insulation manufactured with cyclopentane
- : Fully automated defrost and easily adjustable thermostat
- : All-round magnetic seals to keep the door perfectly shut
- : Interior LED light
- : Lock (can be deactivated)
- : Available size is only 42L
- : Strong drawer slides, drawer can be easily removed
- : Integrated door handles and bespoke wood panel options
- : Can be inserted or stand-alone (Drawer)
- : ISO 9001 2015 / ISO 14001 2015 CE

ASSA ABLOY
Global Solutions

Experience a safer
and more open world

SPECIFICATIONS

| | Polarbar 30 (PB 30) | Polarbar 40 (PB 40) | Polarbar 60 (PB 60) | Polarbar Drawer Unit (PBD 42) |
|--------------------------------------|---|--------------------------------|---------------------------------|--|
| Net Capacity Litres Cu.ft. | 30 1.06 | 40 2.19 | 60 2.19 | 42 1.48 |
| Dimensions H x W x D mm inches | 520x400x425 20,5x15,88x16,7 | 520x400x475 20,5x15,88x18,7 | 526x482x465 21,7x18,97x17,91 | 418 – 550 – 490 16 ^{1/2} – 21 ^{2/3} – 19 ^{2/7} |
| Watts (W) | 65 | 65 | 85 | 65 |
| Voltage (V) | 220/240 | 220/240 | 220/240 | 100/220 |
| Energy Consumption (kWh/24h)(1) | 0,85 | 0,90 | 0,90 | 0,80 |
| Net weight (kgs) (lb) | 15,5 34,1 | 16,5 36,3 | 17,0 38,8 | 18.4 40.56 |
| Certification | ISO 9001 2015 / ISO 14001 2015 CE (ISO/CE/ETL/ERP/WEEE/ROHS2&3) | | | |

ADDITIONAL INFORMATION

- : Ventilation requirements for built-in minibars: a channel for air circulation is imperative for ventilation and operation. A minimum open area of 31 in² (200 cm²)
- : Specifications may change without notice due to continuous product development
- : Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature in compliance with EN ISO 7371

POLARBAR MODELS

